



SOFT LINE S205E

TYPE	Glasswasher
LINE	SOFT LINE
BASKET	350x350
SIZE	420x585x660h

The SOFT line models are equipped with an automatic water softener that offers the possibility to break-down the formation of limestone with extreme efficiency. In fact, the water softener is completely autonomous and automatically controls its regeneration intervals according to the hardness of the inlet water; all you have to do is fill the salt tank whenever the message "lack of salt" appears on the display. The resins are regenerated during wash cycles, so no machine downtime is required. The tempered glass UNIKO-MID lcd-touch display is extremely reliable and ensures optimum performance. Selecting one of the 4 wash cycles available is really simple and practical messages on the display will allow preserving the dishwasher life.

The S205E model, available with round basket or with square basket, is the most appropriate choice to wash cups, saucers and glasses in a very tight space.

The electronic control allows you to manage various parameters to give you an absolute customisation level and the continuous self-diagnosis allows you to minimise machine downtime, suggesting some operations to be verified. The self-cleaning cycle at the end of the day cleans the wash tank and empties the boiler from the hot water, preventing limestone forming inside. The standard double peristaltic electric rinse-aid and detergent dispenser ensures the best result from each wash cycle with great savings thanks to the precise dosage managed by the electronic card; whereas, the moulded washing and rinsing arms ensure great reliability and durability. The Thermo-stop function checks that washing and rinsing begin only when the desired temperature is reached. The bodywork is made entirely of AISI 304 steel and has been designed with all components in the front to allow easy technical assistance. Sturdy and reliable dishwashers to best deal with every moment of your day.

DISHWASHERS FEATURES	SOFT LINE S205E
Dimensions - (mm) L - P - H	420x585x660h
n° baskets/hour - (+55°C)	Max 48
Height glass max	250mm
Rinsing and washing arms	Ø18 INOX
Tank heating element - Tank capacity	2,6kW - 13lt
Boiler heating element - Boiler capacity	2,5kW - 3,2lt
Washing pump (kW-Hp)	0,19kW / 0,25Hp
Total power input / Current	2,79kW / 16A
Standard input voltage	230V 50Hz
Recommended inlet water temperature	+55°C
Water hardness	>15 °f
Water consumption per cycle (inlet suggested pressure 2 BAR)	2,0lt
Adjustable detergent and rinse-aid dispenser	ELECTRIC
Built -in water softener	AUTOMATIC
STANDARD EQUIPMENT	
Basket for glasses dim.350x350x150mm	2
Saucer holder 12 pieces	1
Cutlery insert	1
Salt funnel	1
ACCESSORIES	
UniKo touch display with iCloud Wi-Fi control	✓
Booster pump kit 0,5Hp	-
Drain pump kit 40W	-
Reverse osmosis system	-
Kit 4 Stainless steel feet 50-70mm	✓
2 baskets for glasses Ø350mm	✓

S205E

